Product Data Sheet

5/24/2025

Manifolds, Cabinets & Mixing Groups

Cabinet flush

Romania - Purmo



- · Adjustable Depth
- Height Adjustable Feet
- Zinc-Coated Durability
- Aesthetic Finish
- Secure Lock

Description

Cabinet Flush offers the ultimate solution for housing manifold systems discreetly within walls. The zinc-coated metal structure is durable and long-lasting, with a white RAL 9010 plastic frame and door for a clean look. Height adjustable feet and an adjustable depth mean easy installation in varying wall thicknesses, specifically 80 mm and 120 mm bricks. The cabinet comes with a slotted screwdriver lock, with the option to upgrade to a key lock for added security. This product meets functional demands while maintaining an aesthetic finish.

Area of Application

Cabinet Flush is suitable for flush installation with adjustable depths for 80 mm and 120 mm brick walls. It is designed for applications requiring discreet and secure housing for manifold systems, suitable for both residential and commercial buildings. Supplied with slotted screwdriver locks and height adjustable feet from 0 to 100 mm, users benefit from flexible installation. The frame is flush with plaster for a seamless finish, enhancing aesthetics in hallways, dressing rooms, or boiler rooms.

Selection Criteria

For accurate product selection, you should consider the wall thickness, the required depth, and the dimensions of the intended installation area. For detailed guidance, use our design service or refer to our brochure.

Basic User Instructions

Ensure that the installation area is clean and free from debris before starting. Adjust the height using the adjustable feet to ensure a level installation. Secure the cabinet using the slotted screwdriver lock provided. If opting for the key lock accessory, follow the manufacturer's instructions for installation. Ensure the frame sits flush with the wall plaster to maintain an aesthetic appearance. Regularly check the lock and adjust the feet as necessary to accommodate settling or structural shifts.

Prescription text specifiers

The Cabinet Flush is a zinc-coated metal cabinet designed for flush installation, suitable for brick wall thicknesses of 80 mm and 120 mm. It comes with an adjustable depth feature and height adjustable feet ranging from 0 to 100 mm for accurate leveling. The cabinet includes a slotted screwdriver lock, with an option for a key lock. All visible parts have a white RAL 9010 plastic frame and door, providing a clean, aesthetic finish. Ideal for securely housing manifolds, this cabinet ensures both functionality and style in residential or commercial settings.

Warranty

Specification

Feature	Unit	Value
Etim Class		EC011449 - Group distributor housing
Item weight	Kilogram (kg)	10, 10.68, 10.93, 11.7, 12.45 6.32, 7.5, 7.95,
		8.5, 9.25
Colour		White
Width	Millimetre (mm)	1000, 1050, 1250, 400, 450, 550, 750,
		900
Depth	Millimetre (mm)	110, 120, 130, 160
RAL-number		9016
With mounting plate		Yes
Number of doors		1
Number of locks		1, 2
Suitable for wall mounting		Yes
Material quality		Other, Stainless steel 304 (V2A)
Material		Stainless steel, Steel
Height	Millimetre (mm)	0,3, 0,7, 0,8, 300, 640, 657, 690, 800
Surface finishing		Galvanised, Lacquered
Suitable for floor mounting		No
Suitable for wall built-in		Yes
With door		Yes
Length of legs	Millimetre (mm)	100
Number of groups		1, 12, 2, 3, 5, 9
With pre-stamping for pipes		Yes
With internal insulation		No
Adjustable height		No, Yes
With legs		No, Yes
Weight	Kilogram (kg)	7.32, 9.42

Resources

Document Type **Document Description** Link

Items

Global Item Code	Item Description	
FBWCFS01D3004000	PURMO distributor cabinet Premium line for room control set,	
	flush-mounted	
FBWCFS02A70038P0	Cabinet SWP-0 (2-3 Sections)	
FBWCFS03A70043P0	Cabinet SWP-1 (3-4 Sections)	
FBWCFS06A70055P0	Cabinet SWP-2 (4-7 Sections)	
FBWCFS08A70071P0	Cabinet SWP-3 (7-10 Sections)	
FBWCFS10A70079P0	Cabinet SWP-4 (9-12 Sections)	
FBWCFS12A70096P0	Cabinet SWP-5 (11-14 Sections)	
FBWCFS12A70113P0	Cabinet SWP-6 (12 Sections)	
FF9CFSD0A6904050	PURMO distribution cabinet inWall S flush-mounted, size 1, width 400 mm	
FF9CFSD0A6905050	PURMO distributor cabinet inWall S flush-mounted, size 2, width 500 mm	
FF9CFSD0A6907050	PURMO distribution cabinet inWall S flush-mounted, size 3, width 700mm	
FF9CFSD0A6908550	PURMO distributor cabinet inWall S flush-mounted, size 4, width 850 mm	
FF9CFSD0A6910050	PURMO distribution cabinet inWall S flush-mounted, size 5, width 1000 mm	
FF9CFSD0A6912050	PURMO distribution cabinet inWall S flush-mounted, size 6, width 1200 mm	
FF9CFSD1A6904050	PURMO distribution cabinet inWall flush-mounted, size 1, width 400 mm	
FF9CFSD1A6905050	PURMO distribution cabinet inWall flush-mounted, size 2, width 500 mm	
FF9CFSD1A6907050	PURMO distribution cabinet inWall flush-mounted, size 3, width 700mm	
FF9CFSD1A6908550	PURMO distribution cabinet inWall flush-mounted, size 4, width 850 mm	
FF9CFSD1A6910050	PURMO distribution cabinet inWall flush-mounted, size 5, width 1000 mm	
FF9CFSD1A6912050	PURMO distribution cabinet inWall flush-mounted, size 6, width 1200 mm	