

Residential Air Conditioners X-REVO Wall



Heating performances

Room temperature = 20 °C										
External temperature										
Model	- 15 °C		- 7 °C		2 °C		7 °C		12 °C	
	Ph [kW]	COP	Ph [kW]	COP	Ph [kW]	COP	Ph [kW]	COP	Ph [kW]	COP
X-REVO-0924	1,69	2,19	2,12	3,18	2,46	3,55	2,80	4,18	3,19	4,43
X-REVO-1224	1,81	2,28	2,92	3,02	2,90	3,38	3,30	3,98	3,76	4,22
X-REVO-1824	3,06	2,13	4,60	3,02	5,10	3,38	5,80	3,97	6,61	4,21
X-REVO-2424	5,56	1,93	4,42	2,82	6,60	3,16	7,50	3,71	8,55	3,94
X-REVO-1824D	-	-	4,42	3,14	5,19	3,51	5,90	4,13	6,73	4,38
X-REVO-2423T	-	-	5,13	3,19	7,66	3,57	8,70	4,20	9,92	4,45

TOL = - 20 °C (X-REVO-0924, X-REVO-1224, X-REVO-2424, X-REVO-1824D, X-REVO-2423T models)

TOL = - 15 °C (X-REVO-1824)

Legenda:

Ph: Declared thermal capacity

COP: Coefficient of performance

TOL: Operating temperature limit

Performances according UNI EN 14511 standard