

Product Data Sheet

9/21/2026

Thermostatic Radiator Valves & Heads

TRV2 Thermostatic Head

UK - Myson



- Suitable for Myson TRV2
- Available in Chrome, Anthracite and Black
- Accurate temperature control
- Easy installation
- Compatible with contemporary radiators

Description

Decorative TRV head suitable for Myson TRV2 thermostatic radiator valves. The TRV2 decorative heads add that extra special finishing touch on coloured radiators and towel warmers. Available in Chrome, Anthracite and Black.

Area of Application

The Thermostatic Head 2TRV is suitable for Myson TRV2 thermostatic radiator valves, primarily used in central heating systems with contemporary radiators, including towel radiators. Its polished chrome design adds a touch of elegance.

Selection Criteria

The Thermostatic Head 2TRV is compatible with Myson TRV2. For quick selection use our brochure or design service.

Basic User Instructions

Place the Thermostatic Head 2TRV onto the valve body. Adjust the temperature by rotating the head. Ensure it is securely fitted to prevent leaks. For further guidance, consult the manual or contact our support.

Prescription text specifiers

The Thermostatic Head 2TRV is suitable for Myson TRV2 thermostatic radiator valves. It features a liquid sensor for precise temperature control and comes with a polished chrome finish, offering both functionality and aesthetic appeal. Designed for heating systems in contemporary settings, including towel radiators. Easily fits onto TRV2 valve bodies, enhancing the efficiency and appearance of your heating solution.

General Information

Model: Myson TRV2

Colour: White

RAL Colour Code: RAL 9016

Weight: 0.15 kg

Compatibility

Suitable for Radiators: Yes

Suitable for Heating Systems: Yes

Suitable for Cooling Systems: No

Valve Connection: M30 x 1.5

Thermostatic Element Connection Size: M30 x 1.5

Performance & Control

Sensor Type: Liquid-filled

Temperature Range: 5°C to 28°C

Frost Protection Setting: 8°C (marked with "**")

Frost Protected: Yes

Response Time: 25 minutes

Control Accuracy (CA Value): 0.2 K

Hysteresis: 0.3 K

Water Temperature Influence: 0.55 K

Differential Pressure Influence: 0.7 K

Pressure Ratings

Maximum Static Pressure: 10 bar

Maximum Differential Pressure: 0.6 bar

Features

Zero (Off) Position: Yes

Mechanically Lockable at Off Position: Yes

Vandal Proof: No

Anti-Theft Security: No

Blocking/Limiting Adjustment Range: No

Adjustment Aid for Visually Impaired Users: No

Smart Control Functions
Bluetooth Operation: No
App Control: No
Web Interface: No
Programme Clock: No
Dimensions
Diameter / Height: 45 mm
Length: 94.5 mm

Warranty

For your additional peace of mind, Purmo Group gives the following Warranty against manufacturing defect. Your statutory rights are not affected by this Warranty.

Subject as provided below, Purmo Group warrants to the original purchaser at the original installation site that its products will be free from defects in materials and workmanship for the following periods:

- Hydronic Radiators: 10 years from date of purchase.*
- Fan Assisted Radiators (ULOW-E2): 2 years from date of purchase.*
- Fan Convectors: 2 years from date of purchase.
- Hydronic Underfloor Heating: 10 years for the pipe from date of purchase.
- Hydronic Underfloor Heating: 2 years on accessories, actuators, ball valves, controls, expansion vessels, fittings, low loss headers, manifolds, mixer control groups & tooling from date of purchase.
- Hydronic Underfloor Heating: 12 months on all pumps from date of purchase.
- Electric Underfloor Heating: 10 years from date of purchase (except programmer & sensor).
- Electric Radiators: 10 years from date of purchase on radiator unit*, electric controls & electronic components; 2 years from date of purchase.*
- Electric Towel Warmers: 2 years from date of purchase.*
- Hydronic Towel Warmers: 5 to 10 years from date of purchase depending on product type.*
- Myson Radiator Valves and Controls: 2 to 5 years from date of purchase, depending on range.

*Products which are exposed to prolonged extreme conditions, such as high humidity or severe cold/condensation, may be subject to deterioration. This is not a result of any manufacturing defect. Products installed in these circumstances will be subject to a warranty period of twelve months only.

The original purchaser's remedy for breach of this Warranty is expressly limited to repair or replacement of any part or parts found to be defective under conditions of normal service and use during the above Warranty period and does not extend to Purmo Group being liable for any incidental, special or consequential damages or losses whatsoever, such as loss of use of the product, inconvenience or lost profits.

This Warranty does not cover any defect, damage or malfunction in the product which is due to: failure to comply in any respect with Purmo Group's installation, maintenance or operating instructions; faulty storage,

handling, installation or repair; mis-use; neglect; accident; abuse; or general wear and tear.

Before this warranty can be activated, the original purchaser will be required to prove, with supporting documentation, the date and place of purchase, as Purmo Group may need to conduct its investigation into

the alleged defect. This should be within 28 days of the date when the defect was discovered or ought to have reasonably discovered the defect.

Purmo Group reserves the right to make a reasonable charge for inspecting and testing any product which is subject to a Warranty claim and the rights conferred by the Warranty are

conditional upon the payment of such charge. The charge may be made, at Purmo Group's discretion, either before or after the inspection and testing of the product. In the event that it is established to Purmo Group's reasonable satisfaction that a valid Warranty claim has been made in respect of the product, then any inspection charge which has been paid will be refunded in full by Purmo Group.

Specification

Feature	Unit	Value
Etim Class		EC010064 - Thermostatic control head for valve
Thermostatic adjustment element connection		Other
Connection to valve		M30 x 1.5
Size of thermostatic adjustment element connection		M30 x 1.5
Model		Straight
Suitable for radiator		Yes
Vandal proof		No
With anti-theft security		No
Suitable for heating		Yes
Suitable for cooling		No
Adjustment element		Liquid-filled
Adjustment range min	Degrees celsius (°C)	- 8
Water temperature influence	Kelvin (K)	0.55
Hysteresis	Kelvin (K)	0.3, 0.4
Blocking/limiting adjustment range		No, Yes
With zero (off) position		Yes
Mechanically lockable at zero (off) position		Yes
Frost protected		Yes
Response time	Second (s)	1500
Operation by Bluetooth		No
Operation by app		No
With web interface		No
Programme clock		No
Colour		Chrome, White
Adjustment aid for visually impaired people		No
Width / Length	Millimetre (mm)	52, 94.5
Height	Millimetre (mm)	50, 97
Depth	Millimetre (mm)	52
Differential Pressure Influence	Kelvin (K)	60
Weight	Kilogram (kg)	0.15, 0.16

Resources

Document Description	Document Type	Link
Myson Complete Solutions - Full Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_8031f314-369f-4cf3-af0a-a9fc03976b1b
Myson Valves Brochure	Brochure	https://asset.productmarketingcloud.com/api/assetstorage/3577_ad21f7ac-066f-4cd3-91b8-1099aa73fd9b

Items

Local Code	Global Item Code	Item Description
TRV2TRVHEADCHRO	FD0Z10M3000YHOUK1	Decorative Thermostatic Head Only Chrome
TRV2TRVHEADW	FD0Z10M3000YHOUK3	TRV2 Thermostatic Head Only White
TRV2TRVHEADBLACK	FD0Z10M3000YHOUK5	DEC TRV2 HEAD ONLY BLACK
TRV2TRVHEADANTH	FD0Z10M3000YHOUK6	DEC TRV2 HEAD ONLY ANTH